

styker®

ST-LS



Medical Electric Saw **ST-S6002 Oscillating Saw**

For cutting bone during articular (knee & hip Joint) surgery.

Features

- The primary components are constructed from high-strength stainless steel.
- Capable of withstanding autoclaving at temperatures of up to 135°C for sterilization.
- Features a 3000mAh lithium battery for enhanced power and extended operating periods.
- Weighs less than traditional NI-MH batteries, promoting excellent maneuverability and reducing wrist fatigue.
- Equipped with an imported motor for superior performance.

Components

- 1 handpiece
- 1 charger
- 2 batteries
- 2 battery aseptic transfer rings
- 5 saw blades
- 1 instruction manual
- 1 Aluminum case



Specifications

Main Technical Data

Hand piece	Output power	150W
	Temperature rise	≤25° C
Charger	Input Voltage	AC110-220V, 50-60Hz
Battery	Voltage	14.4V
	Battery capacity	3000mAh
	Battery feature	Lithium Battery
	Charging time	Two hours

Non-loading frequency	0-18000cpm
Non-loading Noise	≤75dB (A)
Swing angle	4±0.5°

Saw Blade - Special Dimensions

Length*Width	Thickness	
50*13	0.8	STB 08-50-13-QX
45*32	1.2	STB 12-45-32-QX
30*10	0.5	STB 05-30-10-QX
28*58	1.0	STB 10-28-58-QX

Saw Blade - Effective length : 90 mm

Length*Width	Thickness	
90 X 24	0.8mm	
	1.0mm	STB 10-90-24-QX
	1.2mm	STB 10-90-24-QX
90 X 22	0.8mm	STB 08-90-22-QX
	1.0mm	STB 10-90-22-QX
	1.2mm	STB 12-90-22-QX
90 X 19	0.8mm	
	1.0mm	STB 10-90-19-QX
	1.2mm	STB 12-90-19-QX
90 X 13	0.8mm	STB 08-90-13-QX
	1.0mm	STB 10-90-13-QX
	1.2mm	STB 12-90-13-QX

Saw Blade - Effective length : 70 mm

Length*Width	Thickness	
70 X 24	0.8mm	
	1.0mm	STB 10-70-24-QX
70 X 22	0.8mm	STB 08-70-22-QX
	1.0mm	
70 X 22	1.2mm	
	1.27mm	STB 127-70-22-QX
70 X 13	0.8mm	STB 08-70-13-QX



Aluminum case packing



Optional Sterilization Case